

For Air

Twist Plug


For pneumatic tools and devices

Working pressure

1.0
1.0 MPa
(10 kgf/cm²)


Valveless

Applicable fluid



Air

Inert gas



Pneumatic tools



Eliminates hose twisting, kinking, or bending! Greatly improves working efficiency!

- A plug with a free twisting neck for hose connections to pneumatic tools and devices.
- Free angle control (max.70° flexible) provides comfortable job positions, even in narrow spaces or with overhead works.
- The flexible part is reinforced with self-lubricating plastics to give smooth bending action and excellent durability.
- Since the flexible part is only in the middle of the plug, connection to the socket is smooth and easy.
- Dust protector over the flexible part prevents dirt and swarf from entering.

Specifications

Body material	Steel (Nickel-plated)			
Size	1/8" • 1/4" • 3/8"			
Working pressure MPa (kgf/cm ²)	1.0 (10)			
Pressure resistance MPa (kgf/cm ²)	1.5 (15)			
Seal material	Seal material	Mark	Working temperature range	Remarks
Working temperature range	Nitrile rubber	NBR (SG)	-5°C~+60°C	Standard material

Tightening Torque Range

N·m (kgf·cm)

Size	R 1/8	R 1/4	R 3/8
Torque	8~10 (82~102)	12~15 (122~153)	22~25 (224~255)

Interchangeability

Can be connected with plugs of Hi Cupla Models 20, 30 and 40.
Interchangeable with each corresponding Hi Cupla Series models.

Suitability for Vacuum

Not suitable for vacuum application in either connected or disconnected condition.


Min. Cross-Sectional Area (mm²)

Model	TS-10PM	TS-20PM	TS-30PM	TS-20PFF
Min. Cross-sectional Area	12.5	38.5	38.5	38.5

Pressure - Flow Characteristics

[Test conditions] • Fluid : Air • Temperature : Room temperature


(S) is a state of straight.
(B) is a state of bending.



Models and Dimensions


WAF : WAF stands for width across flats.

Plug PM type (Male thread)



Model	Application	Mass (g)	Dimensions (mm)			
			Lp	A	øB	T
TS-10PM	Rc 1/8	59	57.5	10	4	R 1/8
TS-20PM	Rc 1/4	59	60	13	8	R 1/4
TS-30PM	Rc 3/8	65	60	13	10	R 3/8

Plug Model TS-20PFF type (Female thread)



- Application : G 1/4
- Mass : 77g