



## ERGONOMICAL "N" TYPE

DESIGNED FOR HEAVY INDUSTRIAL AND MINING APPLICATIONS  
M16 - M50 BOLT CAPACITY

Kuken N Type Impact Wrenches feature -

- Innovative no hammer clutch system
- Excellent power, compactness and light-weight with very low vibration levels
- Low air consumption and noise levels
- Shift-on action ensures less damage to bolts and nuts
- Ergonomical design

Kuken Impact Wrenches for Underground Mining -

- All of Kuken N Type wrenches can be used underground (subject to state approvals)
- Can be stainless steel flow coated for use underground (subject to state approvals)

**KT-1600SPRO**

PISTOL GRIP



**KT-2000P**

PISTOL GRIP



**KT-2500PPRO**

PISTOL GRIP



**KT-2800P**

PISTOL GRIP



**KT-3800P**

PISTOL GRIP



**KT-3800GPRO**

D-HANDLE



**KT-4500P**

PISTOL GRIP



**KT-4500G**

D-HANDLE



**KT-5000G**

D-HANDLE



PART No.	SQUARE DRIVE	BOLT CAPACITY	MAX. TORQUE		SPEED (RPM)	INLET SIZE	WEIGHT (KG)
			(Nm)	(FT/LBS)			
KT1600S PRO	1/2"	16mm	490	360	8,000	1/4"	1.46
KT2000P	3/4"	20mm	850	610	5,000	1/4"	3.1
KT2500P PRO	3/4"	25mm	1150	880	4,500	1/4"	4.2
KT2800P	3/4"	28mm	1380	1000	3,300	1/4"	5.2
KT3800P	1"	38mm	1800	1300	3,700	3/8"	7.4
KT3800G PRO	1"	38mm	1800	1300	4,200	3/8"	6.4
KT4500P	1"	45mm	2750	1980	3,700	1/2"	10.3
KT4500G	1"	45mm	2750	1980	3,700	1/2"	10.7
KT5000G	1-1/2"	50mm	3500	2600	3,000	1/2"	16.0

## CONVENTIONAL HAMMER TYPE

IDEAL FOR ALL HEAVY DUTY APPLICATIONS  
in mining, truck and construction applications

- Deliver extra powerful performances and durability
- Well balanced for easy handling

**KT-18HP**

PISTOL GRIP



**KT-20P**

PISTOL GRIP



**KT-420G**

D-HANDLE



**KT-45F**

D-HANDLE



**KT-75F**

D-HANDLE



PART No.	SQUARE DRIVE	BOLT CAPACITY	MAX. TORQUE		SPEED (RPM)	INLET SIZE	WEIGHT (KG)
			(Nm)	(FT/LBS)			
KT18HP	1/2"	18mm	380	280	7,400	1/4"	2.5
KT20P	3/4"	20mm	700	480	4,500	1/4"	4.2
KT420G	1"	42mm	2900	2200	3,000	1/2"	13.1
KT45F	1-1/2"	45mm	2800	2100	2,800	1/2"	17.6
KT75F	1-1/2"	75mm	6100	4500	2,000	3/4"	38.1

