



POLYURETHANE COILED HOSES

NON-KINKING!
EXCELLENT FLEXIBILITY EVEN AT LOW TEMPERATURES!
LIGHT WEIGHT!



**Hose
Made in USA**



Features

- Oil resistant.
- Excellent memory and stores neatly.
- Small coil diameter stops tangling.
- Straight end sections eliminates hose splitting.
- Hose sizes designed for use with Nitto type nut coupling and fittings, therefore hose clamps are not used.
- No air leakage.

OTHER COMBINATIONS AVAILABLE UPON REQUEST.

SPIRAL HOSE COMPLETE WITH NITTO 200 SERIES NUT CUPLA

Model	Size mm	Working Length
HA0803B	8 x 5	2m
HA0805B	8 x 5	4m
HA0808B	8 x 5	6m
HA0810B	8 x 5	8m
HA1003B	10 x 6.5	2m
HA1005B	10 x 6.5	4m
HA1008B	10 x 6.5	6m
HA1010B	10 x 6.5	8m
HA1203B	12 x 8	2m
HA1205B	12 x 8	4m
HA1208B	12 x 8	6m
HA1210B	12 x 8	8m

NUT CUPLA & NUT CUPLA 200

For fitting to urethane hose

NO HOSE CLAMP REQUIRED!
SIMPLE AND SECURE CONNECTION TO URETHANE HOSE.



Features

- Same series as Hi Cupla and Hi Cupla 200.
- No protruding hose clamping band screw to snag when the hose is moved.
- To fit hose, simply slide it over the nipple and tighten the nut.
- Tightening outside of hose reduces hose slipping or fluid leaking.

PLUG

FOR URETHANE HOSE CONNECTION (PN)



Model	Application
50PN	For ø5 x ø8 hose
65PN	For ø6.5 x ø10 hose
85PN	For ø8.5 x ø12.5 hose
110PN	For ø11 x ø16 hose

SOCKET

FOR URETHANE HOSE CONNECTION (SN)



Model	Application
200-50SN	For ø5 x ø8 hose
200-65SN	For ø6.5 x ø10 hose
200-85SN	For ø8.5 x ø12.5 hose
200-110SN	For ø11 x ø16 hose

HOSE COMBINATIONS

